

MERIT **H<sub>2</sub>**™ HYDROPHILIC GUIDE WIRE

***SLIPPERY WHEN WET***

**GETS YOU THROUGH THE TOUGHEST CURVES**



# Slippery When Wet

## HYDROPHILIC COATING

Increased lubricity enhances catheter tracking. Consistently smooth surface ensures integrity of the coating.

## SOLID NITINOL CORE

Kink resistant core for precise manipulation and steerability in tortuous anatomy with 1:1 torque ratio.

## INCREASED RADIOPACITY

Proprietary polymer technology provides enhanced visibility under fluoroscopy.

## THROMBORESISTANT

A smooth polyurethane jacket and hydrophilic polymer significantly reduce the potential of thrombus formation on the guide wire.

## STIFF SHAFT TECHNOLOGY

Provides strength and stability during catheter placement and exchange.

## AVAILABILITY

Hydrophilic guide wires are available in a variety of diameters, lengths, and tip configurations to ensure the right wire is available for a wide range of diagnostic procedures.

Proprietary manufacturing process with strict process tolerances provide a dependable high performance wire.



## ORDERING INFORMATION:

### HYDROPHILIC STANDARD WIRE CATALOG NUMBERS

<b>H2OSTDA3580</b>	Standard	Angled	.035" (0.89mm)	80cm
<b>H2OSTFA3580</b>	Stiff	Angled	.035" (0.89mm)	80cm
<b>H2OSTDS35150</b>	Standard	Straight	.035" (0.89mm)	150cm
<b>H2OSTDA35150</b>	Standard	Angled	.035" (0.89mm)	150cm
<b>H2OSTDA38150</b>	Standard	Angled	.038" (0.97mm)	150cm
<b>H2OSTFA35150</b>	Stiff	Angled	.035" (0.89mm)	150cm

### HYDROPHILIC SPECIALTY WIRE CATALOG NUMBERS

<b>H2OSTDA35150LT</b>	Standard	Angled	.035" (0.89mm)	150cm	Long Taper
<b>H2OSTDA35180</b>	Standard	Angled	.035" (0.89mm)	180cm	
<b>H2OSTFS35180</b>	Stiff	Straight	.035" (0.89mm)	180cm	
<b>H2OSTFA35180</b>	Stiff	Angled	.035" (0.89mm)	180cm	
<b>H2OSTDA35260EX</b>	Standard	Angled	.035" (0.89mm)	260cm	Exchange
<b>H2OSTFS35260EX</b>	Stiff	Straight	.035" (0.89mm)	260cm	Exchange
<b>H2OSTFA35260EX</b>	Stiff	Angled	.035" (0.89mm)	260cm	Exchange

### HYDROPHILIC SMALL DIAMETER SPECIALTY WIRE CATALOG NUMBERS

<b>H2OSTDA25150</b>	Standard	Angled	.025" (0.64mm)	150cm	
<b>H2OSTDA25180</b>	Standard	Angled	.025" (0.64mm)	180cm	
<b>H2OSTDS25180</b>	Standard	Straight	.025" (0.64mm)	180cm	
<b>H2OSTDA25260EX</b>	Standard	Angled	.025" (0.64mm)	260cm	Exchange
<b>H2OSTDA1880</b>	Standard	Angled	.018" (0.46mm)	80cm	
<b>H2OSTDA18150</b>	Standard	Angled	.018" (0.46mm)	150cm	
<b>H2OSTDA18180</b>	Standard	Angled	.018" (0.46mm)	180cm	
<b>H2OSTDA18260EX</b>	Standard	Angled	.018" (0.46mm)	260cm	Exchange

All hydro wires are fixed core. Hydrophilic guide wires are sold 5 per box.

Torque devices may be purchased separately.

**NOW NEW!**  
**SMALL DIAMETER SPECIALTY WIRES**



Merit Medical Systems, Inc. • 1600 West Merit Parkway, • South Jordan, Utah 84095 • 1-801-253-1600 • 1-800-35-MERIT

www.merit.com

Merit Medical Europe • Horsterweg 24 • 6199 AC MAASTRICHT-AIRPORT • The Netherlands • +31 - 43 - 35 88 222

Merit Medical Ireland Ltd. • Parkmore Business Park West • Galway, Ireland • +353 (0) 91 703 733

Free phone from specific country:

**Belgium** 0800 72906 • **France** 0800 91 60 30 • **Germany** 0800 182 0871 • **Luxembourg** 0800 22522 • **Netherlands** 0800 022 8184 • **UK** 0800 973 115

401814002/B ID 052505